



**TO ORDER:**

REPLACE SQUARES WITH SELECTION FROM EACH TABLE

TABLE: **F** [ ] [ ] [ ] [ ] [ ] [ ] **B2"**

NOTE:  
2" LEADS STD  
B4"=4" LEADS  
"SB" PREFIX FOR  
OPTIONAL  
STRANDED  
LEADS  
SB4=4" STRANDED

**TABLE 1**

ORDER CODE	SHEATH DIAMETER
11	.010"
12	.020"
13	.032"
14	.040"
1	.063"
2	.125"
3	.188"
4	.250"
5	.313"
6	.375"

Other sizes available - consult factory.

**TABLE 2**

CALIBRATION	
SINGLE	DUAL
J	JJ
K	KK
T	TT
E	EE
R	RR
S	SS
B	BB

Add suffix (S) for special limits. i.e. JS  
Consult factory for optional calibration services.  
TRIPLEX MATERIAL AVAILABLE

**TABLE 6**

OPTIONAL MOUNTING FITTINGS		
x = Designates no optional fitting	DESCRIPTION	CODE
	Fits .375 .313 .250" .188" .125"	SL
	1/8 NPT 1/4 NPT 1/2 NPT	A18S A14S A12S
	S = One time adjustable (metal ferrule) T = Readjustable (teflon ferrule)	
	1/8 NPT 1/4 NPT 1/2 NPT 3/4 NPT 1 NPT	F18(x) F14(x) F12(x) F34(x) F38(x)
	Designate (x) dimension in inches.	
	1/2 x 1/2 NPT 1/4 x 1/4 NPT 3/4 x 3/4 NPT	H12(x) H14(x) H34(x)
	Designate (x) dimension in inches.	
	1/8 NPT 1/4 NPT 1/2 NPT 3/4 NPT 1 NPT	B18(x) B14(x) B12(x) B34(x) B38(x)
	Designate (X) dimension in inches.	
	1/2 x 1/2 NPT	HS12(x)
	CONSULT FACTORY FOR OTHER SIZES	
	1/2 x 1/2 NPT	HO12(x)

**TABLE 3**

LENGTH
Refer to illustration above for reference "L" dimension. Specify length in whole and fractional inches. For example: 6 1/2".

**TABLE 4**

ORDER CODE	SHEATH MATERIAL
P	304SS
R	316SS
Q	310SS
J	INCONEL
Y	446SS
T	TANTALUM
O	OTHER

**TABLE 5**

CODE	MEASURING JUNCTION		
G	<table border="0"> <tr> <td>GROUND</td> <td></td> </tr> </table>	GROUND	
GROUND			
U	<table border="0"> <tr> <td>UNGROUND</td> <td></td> </tr> </table>	UNGROUND	
UNGROUND			
UI	<table border="0"> <tr> <td>UNGROUND ISOLATED</td> <td></td> </tr> </table>	UNGROUND ISOLATED	
UNGROUND ISOLATED			
E	<table border="0"> <tr> <td>EXPOSED</td> <td></td> </tr> </table>	EXPOSED	
EXPOSED			
P	<table border="0"> <tr> <td>WELD PAD 1 X 1 X 1/8 std grounded specify ungrounded</td> <td></td> </tr> </table>	WELD PAD 1 X 1 X 1/8 std grounded specify ungrounded	
WELD PAD 1 X 1 X 1/8 std grounded specify ungrounded			

Notes:  
1) Compression fittings: S = Stainless, B = Brass  
Ferrules: metal standard, "T" for teflon (readjustable).  
2) Fixed Fitting: standard stainless steel welded to sheath  
3) Double Fittings: fixed for .062" - .500" O.D.  
4) HO12 available for .188, 250 od only